

PDB DC EV Charger

Floor-Standing LCD 10.1 " touch



60KW/80KW/120KW/160KW

	60KW	80KW	120KW	160KW
Input				
 Power Supply:	3L+PE	3L+PE	3L+PE	3L+PE
Input Voltage:	260~465VAC	260~465VAC	260~465VAC	260~465VAC
MAX Input Current:	120A	160A	240A	320A
Output				
 Output Voltage:	250~1000VDC	250~1000VDC	250~1000VDC	250~1000VDC
MAX Output Current:	0-200A	0-200A	0-250A	0-250A
MAX Output Power:	60KW	80KW	120KW	160KW
User-Friendly Interface				
 LED Indicator:	RGB LED	RGB LED	RGB LED	RGB LED
Display:	LCD Touch 10.1"		LCD Touch 10.1"	
Installation Method:	Floor-Standing	Floor-Standing	Floor-Standing	Floor-Standing
Network connector:	4G/Ethernet/WIFI	4G/Ethernet/WIFI	4G/Ethernet/WIFI	4G/Ethernet/WIFI
IP grade:	IP55	IP55	IP55	IP55
Charging Plug:		CCS2/CCS1/GBT/CHAdeMO		
Cable Length:		5m/customization		
Start Mode:		RFID/OCPP		
Material				
 Housing Material:		Galvanized steel with anti-corrosion painting		
Cable Material:		TPU		

Your Entire Range

To download the entire range and full specifications for our products, please download.

