

PDB DC EV Charger

Floor-Standing LCD 10.1 " touch



60KW/80KW120KW/160KW



Input

	60KW	80KW	120KW	160KW
Power Supply:	3L+PE	3L+PE	3L+PE	3L+PE
Input Voltage:	260~465VAC	260~465VAC	260~465VAC	260~465VAC
MAX Input Current:	120A	160A	240A	320A



Output

Output Voltage:	250~1000VDC	250~1000VDC	250~1000VDC	250~1000VDC
MAX Output Current:	0-200A	0-200A	0-250A	0-250A
MAX Output Power:	60KW	80KW	120KW	160KW



User-Friendly Interface

LED Indicator:	RGB LED	RGB LED	RGB LED	RGB LED
Display:	LCD Touch 10.1"		LCD Touch 10.1"	
Installation Method:	Floor-Standing	Floor-Standing	Floor-Standing	Floor-Standing
Network connector:	4G/Ethernet/WIFI	4G/Ethernet/WIFI	4G/Ethernet/WIFI	4G/Ethernet/WIFI
IP grade:	IP55	IP55	IP55	IP55
Charging Plug:		CCS2/CCS1/GBT/CHAdemo		
Cable Length:		5m/customization		
Start Mode:		RFID/OCPP		



Material

Housing Material:	Galvanized steel with anti-corrosion painting
Cable Material:	TPU



Your Entire Range

To download the entire range and full specifications for our products, please download.

